



turf-slab

With a thickness of 80mm (3.15"), Oaks Turf-Slab is the perfect fit for areas prone to soil or turf erosion. Designed to complement either a granular or natural turf fill, these stones provide stability to pond linings, vehicular access roads, event parking areas and environmentally sensitive locations. In natural color, Turf-Slab can also be mechanically installed, reducing both time and labor costs.



Turf-Slab, Natural



Permeable



Vehicular Traffic

turf-slab

SIZE



Width 400mm (15.76")
Length 600mm (23.62")

COLOR



NATURAL

SPECIFICATIONS

TURF-SLAB	Bundle Specifications					Per Section Specifications				
	Layers	Sq. Ft.	Lin. Ft.	Pieces	Weight	Sections	Sq. Ft.	Lin. Ft.	Pieces	Weight
16x24	6	77.4	59	30	1860	No Sections available				

FEATURES:

- Turf-Slab is manufactured with spacer bars and chamfered edged to prevent chipping
- Each Turf-Slab unit has a 40% void area to allow vegetation growth
- Turf-Slab units are capable of supporting vehicular traffic when installed over a proper base layer

TYPICAL USES:

- Cottage Parking
- Emergency & Service Vehicle Access Routes
- Slope Erosion Protection
- Retention Pond Linings and Vehicular Access Roads
- Ditch & Channel Linings
- High Use Turf Areas like Event Parking and Public Parking Areas
- Environmentally Sensitive Area Erosion Protection
- Small Lake Boat Launching Ramps

Turf Slab fully meets or exceeds the latest version of ASTM 1319 as applicable to the specific product and area of sale.

To find a dealer nearest you please visit:

OAKSpavers.com

Or, call us toll free at:

 **1.800.709.OAKS (6257)** (Canada)

 **1.800.876.OAKS (6257)** (USA)

Members of:



Product representations shown in this publication are intended to convey the general color, texture and appearance of the product. Variations may occur in the manufacturing and printing process. Always select from an actual product sample.